



ADESIVA

Lightweight pasty white coating for repairing holes
INTERIOR / EXTERIOR



DESCRIPTION

Fills holes or cracks of 1mm to 3 cm. In one single coat you can achieve a smooth surface without any defects. Easy to apply and does not require any retouch or finishing. Flexible and resilient product and avoids crack formation.

FIELD OF USE

Fills and hides the surface defects. Protects the finish coats from alkalinity of the cement surfaces. Applies easily and flexibly while drying quickly. ADESIVA applies to all cementitious surfaces, fiber cement, plaster and wood.

TECHNICAL CHARACTERISTICS

- Aspect : Matt
- Colour : White.
- Densité : 0.36 Kg/L +/- 0.05 @ 25°C, complies with NM ISO2811-1(2008).

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- * Sand vigorously with Chiendent brush.
- * Sand with sandpaper.
- * Remove the dust.
- * Wash with a water-jet if necessary.

APPLICATION PROPERTIES

Apply with a spatula or trowel of the following product the thickness of the support to be treated.

Flatten slightly with a spatula or trowel and allow to dry. Apply after drying finish paint of your choice.

Limitation of use : Do not apply on condensing or frozen supports at temperatures below 5 ° C, nor relative humidity above 70%.

APPLICATION DETAILS OF USAGE

Dilution : Ready to use

DRYING TIME

Fast drying depending upon the amount of filler applied (1cm/hour at 25°C).

STORAGE

Two years in the original container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

500 ml and 1 L.

HEALTH & SAFETY

This product is not classified as dangerous according to regulations. For more details, consult the safety data sheet N°35.

Edition : October 2016 by Colorado (10/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001