

## AMBRA M.A.T.

Water-based decorative render based upon a vinyl emulsion  
INTERIOR



### DESCRIPTION

Paint with the highest decorative quality, giving a marble like, traditional finish.

It is especially suitable for big surfaces like halls, dining rooms and flats.

### FIELD OF USE

It is designed for interior decoration.

### TECHNICAL CHARACTERISTICS

- Aspect : Pasty.
- Colors : White, can be tinted with our M.A.T. colorants (see catalogue).
- Spreading-rate : 2 m<sup>2</sup>/kg (2 coats).
- Density : Base P : 1.58 +/- 0.05 Kg/L at 25°C ; Base TR : 1.51 +/- 0.05 Kg/L.
- Viscosity : 1200 poises +/- 200 at 25° C.

### SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- \* Sand vigorously with a Chiendent brush.
- \* Sand with sandpaper
- \* Remove the dust.
- \* Wash with a water-jet if necessary.

### APPLICATION PROPERTIES

Using a roller, apply an even coat of Ambra over the surface.

Before the product dries, spread out the Ambra in all directions using a triangular plastic rendering tool. To reduce the risk of lapping problems, work in areas of 1 to 2 m<sup>2</sup>.

Leave the product for approximately twelve hours to dry. Using a blade or rendering tool, scratch the surface to remove any uneven product.

Apply a second coat of Ambra, without dilution. Ambra should be applied with a suitable trowel.

Wait for three or four hours, lightly sand the surface and clean-up with a wet cloth and then with the special trowel, accentuate the differences in colour to achieve the marble-like effect.

If the trowel is not plastic, it's necessary to protect the blade with a cloth, before use. The use of a steel trowel will leave grey marks on the surface of Ambra. Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

### APPLICATION DETAILS FOR USAGE

Dilution : This product is ready for application. Do not dilute.

### DRYING TIME

12 Hours.

### RECOMMENDED SYSTEM

#### ■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
COLENDUIT EXTRA B805 or SP88	2
COLOVINYL 600	1
AMBRA M.A.T.	2
CIRAGE AMBRA or COLOCIRE (option)	1

### STORAGE

One year in the closed plastic container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures..

### PACKAGING

1 Kg, 4,5 kg.

### HEALTH & SAFETY

This product is not classified as dangerous under current regulations.

For more details, consult the safety data sheet N° 18.

Edition : June 2014 by Colorado (DC 28 D).  
This version replaces all previous editions.