



## BOILUX

Synthetic tinted wood varnish  
INTERIOR / EXTERIOR



### DESCRIPTION

BOILUX is an alkyd based varnish.

### FIELD OF USE

Designed to protect and enhance wood.

### TECHNICAL CHARACTERISTICS

- Aspect : Gloss.
- Colours : 8 tints available (see our catalogue).
- Spreading-rate : 10 to 12 m<sup>2</sup>/L depending upon the type of wood, complies with ISO 23811 (2009).
- % Solids (by weight) : 50% +/- 2%, complies with ISO 3233-3(2015).
- Density : 0.91 kg/L +/- 0.05, complies with NM ISO2811-1(2008).
- Viscosity : 2 min +/- 15 sec with FC6 at 25°C.

### SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry.

### APPLICATION PROPERTIES

BOILUX can be applied by brush, cloth or spray.  
Application limit : Do not apply on cold, wet walls below 5°C or conditions of high relative humidity (> 70%).

### APPLICATION DETAILS OF USAGE

Dilution : D66 (White spirit).

### DRYING TIME

Drying at 25 °C and 60% of humidity :

- \* Touch dry : 1h30
- \* Dry : 8 hours.
- \* Recoatable after 24 hours.

### STORAGE

Two years in the closed original container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures. However, it is recommended to stir the product before to use.

### PACKAGING

750 ML.

### HEALTH & SAFETY

Flammable and harmful product for the human beings and the environment.

For more details consult the Safety data sheet N° 05.

Edition : October 2016 by Colorado (10/16).  
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001