

BOILUX M.A.T.

Synthetic tinted wood varnish
INTERIOR / EXTERIOR



DESCRIPTION

BOILUX is a varnish based upon a modified alkyd resin.

FIELD OF USE

Designed to protect and enhance wood.

TECHNICAL CHARACTERISTICS

- Aspect : Gloss.
- Color : see our catalogue.
- Spreading-rate : 10 to 12 m²/L depending upon the wood nature.
- Density : 0.91 +/- 0.05.
- % Solids (by weight) : 50% +/- 2%.
- Viscosity : 2 min +/- 15 sec with FC6 at 25°C.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry.

APPLICATION PROPERTIES

BOILUX can be applied by brush or spray.
Application limit : Do not apply on cold, wet walls below 5°C or conditions of high relative humidity (> 70%)

APPLICATION DETAILS OF USAGE

Dilution : D33

DRYING TIME

Drying at 25 °C and 60% of humidity :
* Touch dry : 1h30.
* Dry : 8 hours.
* Recoatable after 24 hours.

STORAGE

One year in the closed original container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures. However, it is recommended to stir the product before use.

PACKAGING

750 ML

HEALTH & SAFETY

Flammable and harmful product for the human beings and the environment.
For more details, consult the safety data sheet N° 05.

Edition : June 2014 by Colorado (DC 28 D).
This version replaces all previous editions.