



## CAMELIA MAT

Water-based decorative effect finish  
INTERIOR



### DESCRIPTION

A water-based decorative coating based upon an acrylic resin and special, pearlescent pigments.

### FIELD OF USE

It is designed for interior decoration, giving a subtle, refined finish.  
Depending upon the application tools used, can give a variety of different effects.

### TECHNICAL CHARACTERISTICS

- Aspect : Slightly transparent, pearlescent gel.
- Colors : See our catalogue.
- Spreading-rate : 8 à 10 m<sup>2</sup>/L (in one coat applied by brush, roller or sponge).
- Density : 1.05 Kg/L +/- 0.05 at 25° C.
- Viscosity : 17000 cP +/- 2000 cP at 25° C.
- Solids (by weight) : 30 +/- 1%.

### SURFACE PREPARATION

the surface needs to be clean, sound and dry before rendering.

### APPLICATION PROPERTIES

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering.

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering. Apply over COLOMAT.

Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

### APPLICATION DETAILS FOR USAGE

Dilution : Water.  
Mix well before use.

### DRYING TIME

Drying time at 20°C and 65% relative humidity:

- \* Touch dry : 30 min.
- \* Dry : 5 hours.
- \* Recoatable : 5 hours, if necessary.

### RECOMMENDED SYSTEM

#### ■ INTERIOR

SYSTEM	NUMBRE OF COATS
COLOPRIM	1
COLENDUIT EXTRA B505 ou SP88	2
COLOMAT	1
CAMELIA MAT	2

### STORAGE

Six months in the closed plastic container, as delivered.  
Store inside in conditions avoiding extremes of hot and cold temperatures.

### PACKAGING

\* CAMELIA MAT : 2,5 kg.

### HEALTH & SAFETY

This product is not classified as dangerous under current regulations.

Fore more details, consult the safety data sheet N° 154.

Edition : December 2015 by Colorado (DC 28 D).  
This version replaces all previous editions.