



COLOCRYL SEMI GLOSS

Semi-gloss emulsion paint based on a copolymer acrylic resin

INTERIOR



DESCRIPTION

Semi-gloss emulsion paint based on a copolymer acrylic resin. Contains titanium dioxide, calcium carbonate and water.

FIELD OF USE

COLOCRYL GLOSS is a special, highly resistant interior paint designed to give a smooth, flat finish. It has a good wash resistance.

TECHNICAL CHARACTERISTICS

- Aspect : Smooth, semi-gloss finish.
- Colour : White + Two bases.
- Spreading-rate : 12 to 14 m²/Litre depending upon the porosity of the substrate, complies with ISO 23811 (2009).
- Density : White=1.14 Kg/L +/- 0,05 @ 25°C,
Base P = 1.14 Kg/L +/- 0,05 , Base TR= 1,16 Kg/L +/- 0,05 ,
complies with NM ISO2811-1(2008).
- Viscosity : 105 KU +/- 5 at 25°C, complies with ASTM D561 (1991).

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- * Sand vigorously with Chiendent brush.
- * Sand with sandpaper.
- * Remove the dust.
- * Wash with a water-jet if necessary.

APPLICATION PROPERTIES

Do not apply on cold, wet walls below 5°C or in conditions of high relative humidity, greater than 65%.
Substrate conditions : Sound, dry and well prepared.
Surface preparation : Smooth, clean, dust-free surfaces should be prepared.
Application : Brush or roller. Apply two coats over Colocryl Primer.

APPLICATION DETAILS FOR USAGE

Dilution : Up to 10% water.

DRYING TIME

Drying time at 20°C and 60% relative humidity :

- * Touch dry : 30 min
- * Dry : 2 hours.
- * Recoatable after a minimum 4 hours.

RECOMMENDED SYSTEM (Consult us)

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOCRYL PRIMER	1
COLOCRYL SEMI GLOSS	2

STORAGE

24 months in the closed paint can, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

White : 18 L,
Bases : 0.9 L, 3.6 L, 16.2 L.

HEALTH & SAFETY

This product is not classified as dangerous under current regulations.
For more details, consult the safety data sheet N°122.

Edition : October 2016 by Colorado (09/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001

www.colorado.sa