



COLOPLAST

Vinyl matt paint for economic work
INTERIOR



DESCRIPTION

Interior matt paint based on a vinyl emulsion.

FIELD OF USE

COLOPLAST can be applied over plaster and cement-based renders on interior surfaces, It is designed for economic building work.

TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Colours : Delivered in White, can be tinted with Teintes 2000 colorants.
- Spreading-rate : 4.5 to 5 m²/kg depending upon the porosity of the support, complies with ISO 23811 (2009).
- Density : 1.72 kg/L +/- 0.05 to 25°C, complies with NM ISO2811-1(2008).
- %Solids (by weight) : 73 ± 2%, complies with ISO 3233-3(2015).
- Viscosity : 650 ± 50 Poises at 25°C.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- * Sand vigorously with a Chiendent brush.
- * Sand with sandpaper.
- * Remove the dust.
- * Wash with a water-jet if necessary.

APPLICATION PROPERTIES

COLOPLAST can be applied over plaster and cement-based renders on interior surfaces. It has good whiteness and covering and easy application properties. It is designed for economic work. It is applied with a roller or a brush. Generally, two diluted coats are necessary depending upon the surface porosity.

Over concrete render : One coat of Coloprimer primer + one coat of COLOPLAST two coats of PUTTYMAX pasty render or TOPFILLER + two coats of COLOPLAST.

On plaster : One coat of Formoral primer + two coats of COLOPLAST.

Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

APPLICATION DETAILS FOR USGE

Dilution : Up to 10% water.

DRYING TIME

- * Touch Dry : 15 mn.
- * Through Dry : 1 hour.
- * Recoatable in a minimum 3 hours

RECOMMENDED SYSTEM (Consult us)

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPLAST	1
TOPFILLER / PUTTYLUX	2
COLOPLAST	2

STORAGE

Two years in the closed container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures. However, it recommended to stir the product before to use

PACKAGING

5 kg, 30 kg and 50 kg.

HEALTH & SAFETY

This product is not classified as dangerous under current regulations.

For more details, consult the safety data sheet N° 56.

Edition : October 2016 by Colorado (09/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001