



COLOPOOL

Chlorinated Rubber paint for swimming pools



DESCRIPTION

Chlorinated rubber paint for swimming pools.

FIELD OF USE

COLOPOOL is applied on concrete or for the renovation of already painted swimming pools.

TECHNICAL CHARACTERISTICS

- Aspect : Smooth, satin finish.
- Colour : blue, other tints are available on request.
- Spreading-rate : 5 to 6 m²/Kg, complies with ISO 23811 (2009).
- Density : 1.25 kg/l +/- 0.05 at 25°C, complies with NM ISO2811-1(2008).
- Temperature: resists to 200°C.
- % Solids (weight): 56%, complies with ISO 3233-3(2015).
- % Solids(volume): 36% Thickness: 50 µm.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- * Sand vigorously with a Chiendent brush.
- * Sand with sandpaper
- * Remove the dust.
- * Wash with a water-jet if necessary.

APPLICATION PROPERTIES

COLOPOOL is applied by roller or spray.

- * During application, the temperature should be between 5 to 35 °C.
- *The first coat diluted allows penetration, adhesion and strengthening of the support.
- *The second coat serves to decorate.

APPLICATION DETAILS

- Dilution: Xylene (D77), Toluene (D44), Cellulosic diluant (D33).
- * Brush/roller: 5 to 10%
 - * Spray: 10 to 20%.

DRYING TIME

Drying time at 20°C and 65% relative humidity :

- * Touch dry : 30 min.
 - * Dry : 3 hours.
 - * Recoatable after a minimum 24 hours.
- Allow to dry for 7 days before filling the pool with water.

RECOMMENDED SYSTEM (Consult us)

SYSTEM	NUMBER OF COATS
COLOPOOL	2

STORAGE

One year in the closed paint can, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

5 Kg.

HEALTH & SAFETY

This product is not classified as dangerous under current regulations.
For more details, consult the Safety Data sheet N° 176.

Edition : October 2016 by Colorado (09/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001