



COLOPORE

Hole-filler for wood
INTERIOR / EXTERIOR



DESCRIPTION

Varnish based upon synthetic and nitrocellulose based resins.

FIELD OF USE

COLOPORE is designed to fill holes in wood. It protects the wood from water and sun-light. It has a high viscosity with a high filling power. It does not alter the colour of the wood and prepares the wood for the final varnish finish.

TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Colour : Yellow with a slightly green tone.
- Spreading-rate : 14 to 16 m²/L (depending upon the surface preparation), complies with ISO 23811 (2009).
- Density : 0.95 Kg/l +/- 0,05 at 25°C, complies with NM ISO2811-1(2008).
- Viscosity : 45 +/- 5 mn CF6 at 25°C.

SURFACE PREPARATION

The surface needs to be clean, sound and dry and well prepared.

APPLICATION PROPERTIES

Substrate conditions: For a quick and easy application the surface should be sound, dry and well prepared. Apply directly over the tinted or untinted wood. Brush and Spray application tools are recommended.

APPLICATION DETAILS OF USAGE

Dilution : Diluant Cellulosique D33.

SÉCHAGE

- * Touch dry : 10 to 15 min.
- * Dry : 30 to 40 min.
- *Recoatible after : 1 hour.

STORAGE

Two years in the closed original container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures. However, it is recommended to stir the product before to use.

PACKAGING

0,75 and 4,5 Litres.

HEALTH & SAFETY

Highly flammable product. Can be toxic and harmful to the skin and can cause death if swallowed or if it penetrates the respiratory system. For more details, consult the Safety data sheet N° 97.

Edition : October 2016 by Colorado (10/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001