



COLORBOIS

Tinted wood stain with a fungicide
INTERIOR / EXTERIOR



DESCRIPTION

Tinted, nitrocellulose based wood stain containing a fungicide for protecting and decorating wood.

FIELD OF USE

COLORBOIS is a tinted wood stain containing a fungicide designed for the protection and decoration of interior and exterior wood. It is water resistance and water vapour permeable, stopping the penetration of water but allowing the wood to breath at the same time.

TECHNICAL CHARACTERISTICS

- Aspect : Flat or semi-gloss.
- Colors : See the catalogue.
- Spreading-rate : 10 - 12 sqm/L..
- Density : 0.90 +/- 0.05 Kg/L at 25°C.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry.

APPLICATION PROPERTIES

Recommended application equipment : Brush, cloth and conventional spray, in one or two coats, depending upon the intensity of the tint required.
Finish with 1 or 2 coats of an other varnish (V4, V5, V8 or V9) to protect the wood leaving a glossy surface.
Application limit : Do not apply on cold, wet walls below 5°C or conditions of high relative humidity (>70%).

APPLICATION DETAILS OF USAGE

Dilution : D 33 (cellulosic diluent).

DRYING TIME

Drying at 20 °C and 60% of humidity :

- * Touch dry : 5 minutes.
- * Dry : 30 minutes.
- * Recoatable after 1 hour.

STORAGE

One year in the closed original container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

1 L and 5 L.

HEALTH & SAFETY

Flammable and harmful product.
For more details, consult the Safety data sheet N° 8.