



COPAL

Synthetic varnish for interior wood.
INTERIOR



DESCRIPTION

COPAL is an alcohol-based varnish.

FIELD OF USE

Glossy varnish for interior wood.

TECHNICAL CHARACTERISTICS

- Aspect : Gloss.
- Colour : Transparent.
- Spreading-rate : 12 to 16 m²/L depending upon the wood nature, complies with ISO 23811 (2009).
- Density : 0.97 +/- 0.05 Kg/L to 25°C, complies with NM ISO2811-1(2008).
- % Solids (by weight) : 44% +/- 2%, complies with ISO 3233-3(2015).
- Viscosity : 45 secs +/- 5 with FC4 at 25°C.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry.

APPLICATION PROPERTIES

COPAL can be applied by brush, cloth or spray.
Application limit : Do not apply on cold, wet walls below 5°C or conditions of high relative humidity (> 70%).

APPLICATION DETAILS OF USAGE

Dilution : D33.

DRYING TIME

Drying at 25 °C and 60% of humidity :

- * Touch dry : 20 min.
- * Dry : 1 hour .
- * Recoatable after 3 hours.

STORAGE

Two years in the closed container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures. However, it is recommended to stir the product before to use.

PACKAGING

850 ml and 4.6 L (20 L by order).

HEALTH & SAFETY

Flammable and harmful to human beings and environment.
For more details, consult the Safety data sheet N° 4.

Edition : October 2016 by Colorado (10/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001