



## DECOCRAIE



### DESCRIPTION

DECOCRAIE is a tinted paint which allows writing with chalk. It is ideally suited for walls and furniture in children's bedrooms.

### FIELD OF USE

Paint which allows the easy removal of chalk writing, drawings and designs. Can be used on all types of clean and dry surfaces like walls, wood, metal, and previously painted surfaces prepared with a suitable primer..

### TECHNICAL CHARACTERISTICS

- Aspect : Structured gel.
- Colours : Available in 5 colours, see our catalogue.
- Spreading-rate : Approximately 9 m<sup>2</sup>/Kg ( 12 m<sup>2</sup>/l) in two coats, complies with ISO 23811 (2009).
- Density : 1.30 +/- 0.05 at 25°C, complies with NM ISO2811-1(2008).
- Weight solids : 35 % +/- 2%, complies with ISO3233-3 (2015).
- Viscosity : 7000 +/- 1000 cps at 25°C with the Brookfield Viscosimeter.

### SURFACE PREPARATION

The surface (concrete, cement, tiles) must be dry, sound and clean . if necessary strip the soil to remove any fat.

### APPLICATION PROPERTIES

Mix well before use.  
 For an easy application and optimised spreading rate, the surface must be clean, stable and dry.  
 Application limits : Do not apply over cold or humid surfaces, below 5°C or over 70% relative humidity.  
 Apply one coat of COLOPRIM in order to protect the surface from water absorption and improve the adhesion of paints and renders.  
 Apply two to three coats of COLENDUIT EXTRA B 505 (dry powdered render) or SUPER PATENDUIT SP88 (ready to use, water-based paste render) in order to prepare a smooth, regular surface.  
 Apply one coat of COLOMAT 99 (flat alkyd based paint) or ACRYMAT (water-based acrylic paint).  
 Apply one coat of DECOCRAIE with a gloss paint roller or brush and allow to dry for 4 hours.  
 Apply a second coat of DECOCRAIE.

### APPLICATION DETAILS FOR USAGE

Dilution : Ready to use.

### DRYING TIME

Drying time at 20°C and 60% relative humidity :  
 \* Dry : 2 hours  
 \* Overcoatable after : 4 hours  
 \* Wait 48 hours before writing on the special surface.

### RECOMMENDED SYSTEM (consult us)

#### ■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
COLENDUIT EXTRA B505 or SP 88	2
COLOMAT 99 or ACRYMAT	1
DECOCRAIE	2

### STORAGE

Two years in the closed paint can, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

### PACKAGING

750 ml.

### HEALTH & SAFETY

This product is not classified as dangerous under current regulations.  
 Fore more details, consult the safety data sheet N°110.

Edition : October 2016 by Colorado (10/16).  
 This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certifiéed ISO 9001, ISO 14001 and OHSAS 18001