



# DECOKIDS



## DESCRIPTION

DECOKIDS is a special render which transforms walls and furniture into a magnetic surface allowing metal objects to be attached to it.

## 8,7>6 A8GE7

DECOKIDS can be used over all surfaces which are clean and dry (walls, wood, metal, previously painted surfaces) prepared with a suitable primer.

## F75: @,53>5: 3D35F7D;EF;5E

- Aspect : Flat.
- Colour : gris.
- Spreading-rate : 2 to 3 m<sup>2</sup>/l in one coat, complies with ISO 23811 (2009).
- Density : 2.06 +/- 0.05 at 25°C, complies with NM ISO2811-1(2008).
- Weight solids : 72 % +/- 2%, complies with ISO 3233-3(2015).
- Scrub resistance : Very high.
- Viscosity : 110000 +/- 10000 cps at 25°C with the Brookfield viscometer.

## EGD8357 BD7B3D3F;A@

The surface (concrete, cement, tiles) must be dry, sound and clean . If necessary strip the soil to remove any fat.

## 3BB>;53F;A@BDAB7DF;7E

For an easy application and an optimised spreading rate the surface should be clean, dry and stable.  
 Application limits: Do not apply over cold or humid surfaces,  
 Temperature below 5°C, relative humidity over 70%.  
 Apply one coat of COLOPRIM in order to reduce water absorption and improve adhesion to paints and renders.  
 Apply two or three coats of COLENDUIT EXTRA B 505 (dry powdered render) or SUPER PATENDUIT SP88 (water based pasty render) in order to give a smooth and regular surface.  
 Apply one coat of COLOMAT 99 (flat alkyd based paint) or ACRYMAT (water based acrylic paint).  
 Apply one thick coat of DECOKIDS with a roller and level the coating with a knife or a trowel, then leave to dry for 6 hours.  
 Lightly sand the surface afterwards.

## 3BB>;53F;A@67F3;>E 8ADGE397

Dilution : Ready to use.

## 6DK;@9 F;? 7

Drying time at 20°C and 60% relative humidity :

- \* Surface dry : 4 to 6 hours
- \* Dry : 24 hours
- \* Overcoatable : 24 hours

## D75A?? 7@676 EKEF7? (consult us)

### ■ INTERIAR

SYSTM	NGMBRE A85A3FE
COLOPRIM	1
COLENDUIT EXTRA B505 odSP 88	2
COLOMAT 99 odACRYMAT	1
DECOKIDS	1

## STODAGE

Two years in the closed paint can, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

## B35=39;@9

1 kg and 20 kg.

## : 73>F: ~ E387FK

This product is not classified as dangerous under current regulations.  
 Fore more details, consult the safety data sheet N°102.

Edition : October 2016 by Colorado (10/16).  
 This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.