



# DECOTERRE

Decorative earth effect  
INTRIAR



## DESCRIPTION

Decorative earth effect.

## 87>6 A8GE7

Decorative earth effect. Application limits: Do not apply over cold or humid surfaces, Below 5°C, Relative Humidity over 70%.

## F75: @;53>5: 3D35F7D;EF;5E

- Aspect : Base Product.
- Colours : Various shades available.
- Spreading rate : 1 m<sup>2</sup>/Kg (in one coat), complies with ISO 23811 (2009).
- Density : 1.6 +/- 0.01 Kg/L at 25°C, complies with NM ISO2811-1(2008).
- Weight solids : 67 +/- 2%, Complies with ISO 3233-3(2015).

## EGD8357 BD7B3D3F;A@

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- \* Sand vigorously with a Chiendent brush.
- \* Sand with sandpaper.
- \* Remove the dust.
- \* Wash with a water-jet if necessary.

## 3BB>;53F;A@BDAB7DF;7E

Apply by trowel over a previously prepared surface (one or two coats of COLOPRIM applied over a dry, sound, dust free surface).

Apply two or three coats of TOPFILLER (dry powdered render) or PUTTYMAX (water based paste render) in order to prepare a smooth and regular surface.

Apply one coat of ROYALKYD MATT (flat, alkyd based paint) or COLOCRYL MATT (water based acrylic).

Apply one coat of COLOFONDO (priming coat) based upon the desired DECOTERRE colour and leave to dry for 12 hours. Application Aspect Terre or Earth effect.

Apply DECOTERRE with the aid of a metal trowel with circular, crossed, irregular movements in order to obtain a more or less structured texture. Leave for 30 minutes then slightly humidify the surface (about 2 m<sup>2</sup> at the time) with a sponge. Then with a stainless steel trowel, reduce the surface texture by pressing the surface. With a metal brush, create different effects.

In order to better protect DECOTERRE outside, it is recommended to apply one coat of the Varnish VERNIS DECOTERRE. Please note that this will slightly darken the colour.

Do not apply over wall paper.

Application limits: Do not apply over cold or humid surfaces, Below 5°C, Relative Humidity over 70%.

## 61 F3;>E 67>3? ;E77@A7GHD7

Dilution : Ready to use.

## 6DK;@9 F;? 7

We recommend that each room is applied in one go in order to avoid any slight color differences.

At 20 °C and 60 % relative humidity :

- \* Initial surface: 30 minutes.
- \* Through dry : 48 hours.

## D75A? ? 7@676 EKEF7? (Consult us)

### ■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
TOPFILLER OR PUTTYMAX	1
COLOFONDO	1
DECOTERRE	1
COLOPRIM (Option)	1

## EFAD397

24 months in the original container stored away from the cold and the sun.

## B35=39;@9

7 Kg. 73>F: 7

## E387FK

Decorative earth effect. Application limits: Do not apply over cold or humid surfaces, Below 5°C, Relative Humidity over 70%.

Edition : October 2016 by Colorado (09/16).  
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO [certified] ISO 9001, ISO 14001 ~ OHSAS 18001