



FLEXOMAT

Flexible, water resistant masonry paint
EXTERIOR



DESCRIPTION

Flexible, water resistant masonry paint based on acrylic resins.

FIELD OF USE

FLEXOMAT is water resistant, flexible and water proofing. It has excellent flexibility and resistance properties to various temperatures and weather conditions. Designed for interior and exterior masonry.

TECHNICAL CHARACTERISTICS

- Aspect : Matt and smooth.
- Colours : Delivered in white, red oxide.
- Spreading-rate : 2 Coats :
With Coloprime : 3 m²/Kg.
Without Coloprime : 2.5m²/Kg.
Complies with ISO 23811 (2009).
- Density : 1.66 +/- 0.05 Kg/L to 25°C, complies with NM ISO2811-1(2008).
- % weight solids : 71+/- 2% depending upon the colour, complies with ISO 3233-3(2015).
- Viscosity : 560 +/- 50 Poises at 25°C with the BrookField.

SURFACE PREPARATION

The surface needs to be clean, sound and dry before painting. If necessary, clean and repair any surface irregularities before starting the paint job, making sure that the surface is clean.

APPLICATION PROPERTIES

Application hardware : Brush, Roller and Spray.
Use instructions : Over porous surfaces the 1st coat should be diluted with up to 50% of water. If not, apply two or three overlapping coats without dilution.
Application limit : Do not apply on cold wet walls below 5°C or conditions of high relative humidity (>70%).

APPLICATION DETAILS OF USAGE

Dilution : Water.

DRYING TIME

- * Dry : 6 hours.
- * Recoatable after 24 hours.

RECOMMENDED SYSTEM (consult us)

■ EXTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM (option)	1
FLEXOMAT	2

STORAGE

Two years in the closed container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures. However, it is recommended to stir the product before to use.

PACKAGING

1 Kg, 5 Kg and 20 Kg.

HEALTH & SAFETY

This product is not classified as dangerous according to regulations.
For more details, consult the safety data sheet N°59.

Edition : October 2016 by Colorado (10/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001