



## FORMORAL

Primer / Undercoat  
INTERIOR / EXTERIOR



### DESCRIPTION

Alkyd-based undercoat paint.

### FIELD OF USE

Interior primer/undercoat which enables a one-coat finish to be achieved.  
FORMORAL can be applied over plaster and wood substrates, to equalise the absorption properties for the final, finishing coat.

### TECHNICAL CHARACTERISTICS

- Aspect : Satin.
- Colours : White.
- Spreading-rate : 4 to 5 m<sup>2</sup>/kg depending upon the porosity of the substrate, complies with ISO 23811 (2009).
- Density : 1.57 Kg/L ± 0.05 at 25°C, complies with NM ISO2811-1(2008).
- % Solids ( by weight ) : 81 % +/- 2%, complies with ISO 3233-3(2015).
- Viscosity : 100 KU +/- 5 @ 25 °C (Krebs - Stormer), complies with ASTM D561 (1991).

### SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- \* Sand vigorously with Chiendent brush.
- \* Sand with sandpaper.
- \* Remove the dust.
- \* Wash with a water-jet if necessary.

### APPLICATION PROPERTIES

Do not apply on cold, wet walls below 5°C or in conditions of high relative humidity, greater than 70%.  
Substrate conditions : For a quick and easy application the surface should be sound, dry and well prepared.  
A well prepared surface allows the gloss paint spreading-rate to be optimised.  
Application : FORMORAL can be applied by brush, roller or spray.

### APPLICATION DETAILS FOR USAGE

Dilution : D66 (White Spirit ).

### DRYING TIME

Drying time at 20°C and 60% relative humidity :  
\* Touch dry : 30 minutes  
\* Dry : 5 hours  
\* Recoat after 12 hours.

### STORAGE

Two years in the closed paint can, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures. Keep away from sources of heat, sparks and flames.

### PACKAGING

5 and 30 Kg.

### HEALTH & SAFETY

Flammable product and toxic to humans and the environment.  
For more details, consult the safety data sheet N° 96.

Edition : October 2016 by Colorado (10/16).  
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001