TECHNICAL DATA SHEET



KANZ M.A.T

Water-based decorative effect finish INTERIOR



67E5D;BF;A@

KANZ is a water-based decorative effect finish with a metallic sand finish with sparkling effect pigments.

FIELD OF USE

It is designed for interior decoration, giving a coloured, stylish, scintillating effect on walls. It is especially suitable for big surfaces like halls, dining rooms and flats.

TECHNICAL CHARACTERISTICS

- Aspect : Scintillating, flat effect.
- Colours: See our Tinting machine catalogue.
- Spreading-rate : About 12 m²/Kg.
- Density: 1.27+/- 0.05 Kg/L at 25° C for the neutral base.
- Viscosity: About 30000 cP with the Brookfield S6/10 @ 25°C for the neutral base.

APPLICATION PROPERTIES

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering.

Using a brush or roller, apply over COLOFONDO an even coat over the surface.

Apply a second coat in the same way. Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

APPLICATION DETAILS FOR USAGE

Dilution: This product is ready for application (can be diluted with upto 5% of water).

Mix well before use.

DRYING TIME

Prepare the surface with one or two coats of Colofondo (preferably tinted) or ACRYMAT and leave to dry for 12 hours:

Drying time at 20°C and 65% relative humidity:

- * Touch dry: 1 hour.
- * Dry: 4 hours.
- * washable: 20 days.

STORAGE

One year in the closed plastic container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

2.5 Kg net.

HEALTH & SAFETY

Do not leave near children. Do not digest. Do not throw un-used product into the public sewage system. See the safety data sheet for further information.

Edition: March 2016 by Colorado (DC 28 D). This version replaces all previous editions.