



POREX

Hole-filler for wood
INTERIOR / EXTERIOR



DESCRIPTION

POREX is designed to fill holes. It protects wood from humidity and sun-light. It does not alter the colour of the wood and prepares the wood for the final varnish finish.

FIELD OF USE

Recommended to prepare wood work.

TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Colour : Transparent.
- Spreading-rate : 12 to 14m²/L depending upon the preparation of the surface, complies with ISO 23811 (2009).
- Density : 0.97 Kg/L ± 0,02 at 25°C, complies with NM ISO2811-1(2008).
- % Solids (by weight) : 37 +/-2 %, complies with ISO 3233-3(2015).
- Viscosity : 3mn FC6 at 25°C.

SURFACE PREPARATION

The surface needs to be clean, sound and dry and well prepared.

APPLICATION PROPERTIES

Can be applied directly on tinted or not tinted wood.
Application limit : Do not apply on cold, wet walls below 5°C or conditions of high relative humidity (> 70%).

APPLICATION DETAILS OF USAGE

Dilution : D33.

DRYING TIME

Drying at 20 °C and 60% of humidity :

- * Touch dry : 10 to 15 min.
- * Dry : 30 to 40 min.
- * Recoatable after 1 hour.

STORAGE

One year in the closed original container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures. However, it is recommended to stir the product before to use.

PACKAGING

0,75 L, 5L and 20 L.

HEALTH & SAFETY

Highly flammable product. Can be toxic and harmful to the skin and can cause death if swallowed or if it penetrates the respiratory system.
For more details, consult the Safety data sheet N° 03-2.

Edition : October 2016 by Colorado (10/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001