



## PUTTYFLEX

Hydraulic powdered render for reating humidity  
INTERIOR / EXTERIOR



### DESCRIPTION

Powdered render based on a hydraulic binder and special extenders and a special hydrophobic resin. Stops humidity (class W3). Lets the support breath.

### FIELD OF USE

Designed for retouching and finishing work on interior/exterior masonry, wet or humid such as cement, concrete, bricks or stone. Repairs holes up to 1 cm thick.

### TECHNICAL CHARACTERISTICS

- Aspect : Powder.
- Colour : White.
- Spreading-rate : 1.5 Kg/m<sup>2</sup> by mm of thickness, complies with ISO 23811 (2009).

### SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- \* Sand vigorously with Chiendent brush.
- \* Sand with sandpaper.
- \* Remove the dust.
- \* Wash with a water-jet if necessary.

Remove any traces of algal or fungal growth before applying. Rinse if necessary with a fungicidal solution, then leave to dry before applying ENDUIFLEX.

### APPLICATION PROPERTIES

Recommended hardware: coating knife/spatula.

Apply for 2 coats depending upon the desired film thickness.

Apply an even coat over the surface.

In order to obtain an efficient protection, apply at least 2 mm of thickness in a regular way.

Recommended system:

	Number of coats
* PUTTYFLEX	2 (2 mm minimum)
* COLOPRIM	1

Limitation of use : Do not apply on condensant or frozen support at temperature below 5°C, or above 40°C relative humidity above 70%.

### APPLICATION DETAILS FOR USAGE

Water (approximately 30%). Mix well and leave for 15 minutes, then mix again before applying.

### DRYING TIME

Drying at 20°C and 60% of humidity :

\* Recoat : 24 hours.

### RECOMMENDED SYSTEM (Consult us)

#### ■ INTERIOR / EXTERIOR:

SYSTEM	NUMBER OF COATS
PUTTYFLEX	1 to 2

### STORAGE

Tow years in the closed original container. Store inside in conditions avoiding extremes of hot and cold temperatures.

### PACKAGING

5 kg.

### HEALTH & SAFETY

For more details, consult the safety data sheet N° 175.

Edition : October 2016 by Colorado (09/16).  
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001