



## PUTTYLUX

Pasty render for economic interior work  
INTERIOR



### DESCRIPTION

PUTTYLUX is a thick, pasty water-based render based upon a vinyl emulsion. It is designed for interior economic housing work.

### FIELD OF USE

It is designed for retouching and covering surface irregularities. It protects against surface alkalinity with fresh cement. Easy application properties combined with fast drying. It can be applied over all the typical surfaces: cement, fibre cement, plaster board, plaster and wood.

### TECHNICAL CHARACTERISTICS

- Aspect : Smooth, matt finish.
- Colour : Grey, very pasty product.
- Spreading-rate : \* As a filler : 2 at 3 m<sup>2</sup>/kg  
\*As a render : 3 at 4 m<sup>2</sup>/kg.  
Complies with ISO 23811 (2009).
- Density : 1.73 Kg/L +/- 0.05 at 25° C, complies with NM ISO2811-1(2008).
- Viscosity : 1100 +/- 300 poises at 25° C Brookfield.

### SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- \* Sand vigorously with a Chiendent brush.
- \* Sand with sandpaper.
- \* Remove the dust.
- \* Wash with a water-jet if necessary.

### APPLICATION PROPERTIES

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering. It is recommended to apply first coat of the vinyl matt emulsion paint, immediately after the drying of the second coat of PUTTYLUX. It should be applied with a suitable trowel. Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

### APPLICATION DETAILS OF USAGE

Dilution : Ready to use.

### DRYING TIME

Drying time at 20°C and 60% relative humidity :  
\*Touch dry : 30 min +/- 10 min.  
\* Dry: 1 H +/- 10 min.

### RECOMMENDED SYSTEM (Consult us)

#### ■ INTERIOR

SYSTEM	NUMBER OF COATS
PUTTYLUX	1 to 2

### STORAGE

24 months in the closed plastic bag, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

### PACKAGING

25 kg.

### HEALTH & SAFETY

This product is not classified as dangerous according to regulations. For more details consult the safety data sheet N°173.

Edition : October 2016 by Colorado (09/16).  
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001