



PUTTYMAX

Pasty render for standard interior work
INTERIOR



DESCRIPTION

PUTTYMAX is a water-based render based upon a vinyl emulsion.

FIELD OF USE

Can be applied over cementitious substrates, fiber cement, plaster and wood. It has a high covering power and easy application properties. It fills-in and covers over any surface imperfections and protects against the alkalinity of cementitious surfaces.

TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Colour : Grey, very pasty product.
- Spreading-rate : * As a filler : 2 at 3 m²/kg.
* As a render : 3 at 4 m²/kg.
Complies with ISO 23811 (2009).
- Density : 1.75 Kg/L +/- 0.05 at 25° C, complies with NM ISO2811-1(2008).
- Viscosity : 3800 +/- 200 poises at 25° C.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- * Sand vigorously with a Chiendent brush.
- * Sand with sandpaper.
- * Remove the dust.
- * Wash with a water-jet if necessary.

APPLICATION PROPERTIES

Applied using a spatula. For easy application and optimum performance the surface needs to be clean, sound, dry and smooth before rendering. Do not apply in wet conditions, with temperatures below 5°C and/or relative humidity over 70%.

APPLICATION DETAILS OF USAGE

Dilution : Up to 10% water.

DRYING TIME

At 20°C and 60% Relative Humidity :

- *Touch dry: 30 min +/- 10.
- * Dry: 60 min +/- 10.

RECOMMENDED SYSTEM (Consult us)

■ INTERIOR:

SYSTEM	NUMBER OF COATS
PUTTYMAX	1 to 2
COLOCRYL PRIMER	2

STORAGE

24 months in the closed plasticbag, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

25 Kg.

HEALTH & SAFETY

This product is not classified as dangerous according to regulations.

For more details consult the safety data sheet N° 127.

Edition : October 2016 by Colorado (09/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001