



SICILIA

Water-based decorative effect finish
INTERIOR



DESCRIPTION

Sicilia is a decorative paint that combines Sicilian art with a contemporary trend in Morocco. It offers easy application and applied to the base product COLOFONDO.

FIELD OF USE

It is designed for interior decoration, giving a coloured, pearlescent effect on walls. It is especially suitable for big surfaces like halls, dining rooms and flats.

TECHNICAL CHARACTERISTICS

- Aspect : Special coloured Pearlescent effect.
- Colours : See our catalogue.
- Spreading-rate : 7.5 to 8.6 m² /L, complies with ISO 23811 (2009).
- Density : 1.07 kg/l +/- 0.05 depending upon the colour at 25°C, complies with NM ISO2811-1(2008).
- Viscosity : 108 KU's +/- 10 at 25°C, complies with ASTM D561 (1991).

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- * Sand vigorously with a Chiendent brush.
- * Sand with sandpaper.
- * Remove the dust.
- * Wash with a water-jet if necessary.

APPLICATION PROPERTIES

Using the special brush, apply SICILIA in all directions over the surface. To reduce the risk of lapping problems, work in areas of 1 to 2 m². Leave the product for approximately ten minutes to dry. Using a blade or rendering tool, spread out the product in order to obtain the special effect.

APPLICATION DETAILS FOR USAGE

Dilution : This product is ready for application. Do not dilute. Mix well before use.

DRYING TIME

Drying time at 20°C and 60% relative humidity :
* Touch dry : 3 to 4 hours
* Dry : 24 hours
* Washable : 20 days

RECOMMENDED SYSTEM (consult us)

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
COLENDUIT Extra B505 ou SP88	2
COLOVINYL 600	1
COLOFONDO	1
SICILIA	1

STORAGE

Six months in the closed plastic container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

SICILIA : In 2 L containers.
COLOFONDO TEINTE : In 1.6 L containers.

HEALTH & SAFETY

This product is not classified as dangerous under current regulations. For more details, consult the safety data sheet N°99.

Edition : October 2016 by Colorado (10/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001