# **TECHNICAL DATA SHEET**



# STELLA M.A.T.

Water-based decorative effect finish INTERIOR

# DESCRIPTION

STELLA is a water-based acrylic copolymer decorative effect finish.

# FIELD OF USE

It is designed for interior decoration, giving a colored, pearlescent effect on walls with a scintillating special effect.

It is especially suitable for big surfaces like halls, dining rooms and flats.

### **TECHNICAL CHARACTERISTICS**

- Aspect : Colored, slightly Metallic and Pearlescent effect.
- Colors : See our catalogue.
- Spreading-rate : About 7 m<sup>2</sup>/L (in 2 coats).
- Density : 1.15 Kg/L +/- 0.05 for argent base at 25° C.
- Viscosity : 108 KU's +/- 10 at 25° C (Kreb Stormer).

# SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- \* Sand vigorously with a Chiendent brush.
- \* Sand with sandpaper
- \* Remove the dust.
- \* Wash with a water-jet if necessary.

#### APPLICATION PROPERTIES

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering.

Using a roller, apply an even coat of Colofondo (Tinted) over the surface. Let the Colofondo dry for 12 hours.

Using the special short pile roller, apply Stella (diluted with 20% of water) in all directions over the surface. To reduce the risk of lapping problems, work in areas of 1 to  $2 \text{ m}^2$ .

Leave the product to dry.before applying a second diluted coat (and if necessary a third coat) using the short pile roller. Using a blade or rendering tool, spread out the Stella in order to obtain the special effect.

Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

#### APPLICATION DETAILS FOR USAGE

Dilution : This product is ready for application. Mix well before use. Depending upon the application method used, this product can be diluted with upto 20% of tap water

#### DRYING TIME

Drying time at 20°C and 60% relative humidity: \* Touch dry : 3 to 4 hour.s

- \* Dry : 24 hours.
- \* Washable : 20 days.

#### **RECOMMENDED SYSTEM**

#### INTERIOR

SYSTEM	NUMBRE OF COATS
COLOPRIM	1
COLENDUIT EXTRA B505 ou SP88	2
COLOVINYL 600	1
COLOFONDO	1
STELLA	2

#### **STORAGE**

Six months in the closed plastic container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

#### PACKAGING

\*STELLA: 2 Litres. \*COLOFONDO : 1.6 litres.

#### **HEALTH & SAFETY**

This product is not classified as dangerous under current regulations.

For more details, conult the safety data sheet N° 98.

Edition : June 2014 by Colorado (DC 28 D). This version replaces all previous editions.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001