



# STUCCO KSOUR M.A.T.

Water-based decorative render giving a marble like finish  
INTERIOR/EXTERIOR

## DESCRIPTION

KSOUR is a water-based decorative render based upon an acrylic emulsion.  
Contains a fungicide.

## FIELD OF USE

It is designed for exterior decoration (due to its anti-fungal properties), giving a marble like, traditional finish. It has a high degree of whiteness and excellent scrub resistance.

## TECHNICAL CHARACTERISTICS

- Aspect : Pasty render.
- Colors : Blanc, teintes : see our catalogue.
- Spreading-rate : 3 to 4 m<sup>2</sup> / kg (2 Coats).
- Density : 1.54 +/- 0.05 Kg/L to 25°C.
- Viscosité : 1000 poises +/- 200 to 25°C.

## SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- \* Sand vigorously with a Chiendent brush.
- \* Sand with sandpaper
- \* Remove the dust.
- \* Wash with a water-jet if necessary.

## APPLICATION PROPERTIES

Using a roller, apply an even coat of Stucco Ksour over the surface.

Before the product dries, spread out the Stucco Ksour in all directions using a triangular plastic rendering tool. To reduce the risk of lapping problems, work in areas of 1 to 2m<sup>2</sup>.

Leave the product for approximately seven hours to dry. Using a blade or rendering tool, scratch the surface to remove any uneven product.

Apply a second coat of Stucco Ksour, without dilution. Stucco Ksour should be applied with a suitable trowel. Wait for three or four hours and then with the special trowel, accentuate the differences in colour to achieve the marble-like effect.

If the trowel is not plastic, it's necessary to protect the blade with a cloth, before using. The use of a steel trowel will leave grey marks on the surface of Ksour. Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

Edition : June 2014 by Colorado (DC 28 D).  
This version replaces all previous editions.

## APPLICATION DETAILS FOR USAGE

Dilution : This product is ready for application. Can be diluted with water.

## DRYING TIME

- \*1st coat : 12h
- \*2nd coat : 4h

## RECOMMENDED SYSTEM

### ■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
COLENDUIT EXTRA B505	2
COLOVINYL 600	1
STUCCO KSOUR M.A.T.	2

### ■ EXTERIOR

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20	1
COLOPRIM	1
COLOVINYL 600	1
STUCCO KSOUR M.A.T.	2

## STORAGE

One year in the closed paint can, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

## PACKAGING

5 kg, 10kg and 25kg

## HEALTH & SAFETY

This product is not classified as dangerous under current regulations.  
For more details, consult the safety data sheet N° 21.