



## TOPFILLER

Coating powder for interior renders based vinyl copolymers



### DESCRIPTION

It is a tender which gives a smooth and uniform finish. It protects against surface alkalinity with fresh cement.

### FIELD OF USE

It is designed for interior work. the render gives a smooth and uniform finish.

### TECHNICAL CHARACTERISTICS

- Aspect : Matt finish.
- Spreading-rate : First coat : 3 to 4 m<sup>2</sup>/kg,  
Second coat : 2 to 3 m<sup>2</sup>/kg,  
Complies with ISO 23811 (2009).
- % Solids ( by weight ) : 100%, complies with ISO 3233-3(2015).

### SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- \* Sand vigorously with Chiendent brush.
- \* Sand with sandpaper.
- \* Remove the dust.
- \* Wash with a water-jet if necessary.

### APPLICATION PROPERTIES

Recommended hardware: spatula, trowel or coating knife.  
Limitation of use : Do not apply on condensant or frozen support at temperature below 5 ° C, nor relative humidity above 70%.

### APPLICATION DETAILS FOR USAGE

Requires a dilution up to 40%.

### DRYING TIME

1st coat : 1 hour.  
2nd coat : After 24 hours.

### RECOMMENDED SYSTEM (Consult us)

#### ■ INTERIOR:

SYSTEM	NUMBER OF COATS
TOPFILLER	1 to 2
COLOCRYL PRIMER	1

### STORAGE

24 months in the closed original container. Store inside in conditions avoiding extremes of hot and cold temperatures.

### PACKAGING

25 kg

### HEALTH & SAFETY

This product is not classified as dangerous under current regulations.  
For more details, consult the safety data sheet N°120.

Edition : October 2016 by Colorado (09/16).  
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001