



VERNIS GRAS V804

Synthetic varnish
INTERIOR



DESCRIPTION

Varnish based on a modified synthetic resin.

FIELD OF USE

Designed to protect and enhance exterior wood.

TECHNICAL CHARACTERISTICS

- Aspect : Gloss.
- Colour : Transparent.
- Spreading-rate : 9 to 11 m²/L, complies with ISO 23811 (2009).
- Density : 0.92 +/- 0.05 Kg/l at 25°C, complies with NM ISO2811-1 (2008).
- Viscosity : 50 sec with FC6 at 25°C.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound, dry and well prepared.

APPLICATION PROPERTIES

Application equipment : Brush, roller and pneumatic spray.
Apply a coat of 10% drier modified linseed oil.
Sand and dust.
Apply a coat of V804 diluted 5%.
Allow to dry at least 24 hours.
Apply a second coat of V804.
Application limit : Do not apply on cold, wet walls below 5°C or conditions of high relative humidity (>70%).

APPLICATION DETAILS OF USAGE

Dilution : D66 (white spirit).

DRYING TIME

- * Touch dry : 3 hours.
- * Dry : 12 hours.

STORAGE

Two years in the closed original container, as delivered.
Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

850 ml and 4,6 L.

HEALTH & SAFETY

Flammable and harmful product for human beings and environment.
For more details, consult the Safety data sheet N° 06.

Edition : October 2016 by Colorado (10/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001