




IMPREX

Impregnation varnish based on modified synthetic binders.
INTERIOR / EXTERIOR



DESCRIPTION

Imprex is designed to water-proof masonry surfaces. It is a new generation of selective waterproofing products, combining water resistance with water vapour permeability.

FIELD OF USE

Recommended for application on exterior and interior masonry walls.

TECHNICAL CHARACTERISTICS

- Aspect : Satin.
- Colour : Transparent.
- Spreading-rate : 14 to 16 m² after dilution with 100 % of white spirit, complies with ISO 23811 (2009).
- Density : 0.90 +/- 0.05 Kg/L at 25°C, complies with NM ISO2811-1(2008).
- % Solids (by weight) : 30 +/- 2%, complies with ISO 3233-3(2015).
- Viscosity : 45 seconds +/- 10 with the Ford Cup Number 6 at 25°C.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering. Eliminate the causes of the humidity before starting to remedy its effects.

APPLICATION PROPERTIES

Is applied by roller or brush.
Limitation of use: Do not apply on condensing or frozen support at temperatures below 7 ° C, nor relative humidity above 70%.

APPLICATION DETAILS FOR USAGE

Dilution : D66 (WHITE SPIRIT).

DRYING TIME

Drying at 20°C and 60% relative humidity :

- *Touch dry : 20 min
- *Dry : 1h30
- *Recoverable : after 3h

STORAGE

Two years in the closed original container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures., however it is recommended to stir the product before use.

PACKAGING

1.5 and 20 liters.

HEALTH & SAFETY

Flammable product and toxic to humans and the environment.
For more details, consult the safety data sheet N° 07 .

Edition : October 2016 by Colorado (10/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001