



VERNIS MARIN V9

Glossy transparent synthetic varnish
INTERIOR / EXTERIOR



DESCRIPTION

VERNIS V9 MARIN is a transparent, synthetic, glossy varnish resistant to UV.

FIELD OF USE

Synthetic interior and exterior varnish, leaving a smooth, glossy film. It is particularly suitable for high quality decoration, but needs to be applied over clean, dust-free wood.

TECHNICAL CHARACTERISTICS

- Aspect : Glossy and smooth.
- Colour : Transparent.
- Spreading-rate : 10 - 12 m²/L, complies with ISO 23811(2009).
- Density : 0.90 +/- 0.05 Kg/L at 25°C, complies with NM ISO2811-1(2008).
- Viscosity : 1 mn +/- 10 sec with FC6 at 25°C.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry.

APPLICATION PROPERTIES

Recommended application equipment : Brush, roller and conventional spray.
Application limit : Do not apply on cold, wet walls below 5°C or conditions of high relative humidity (>70%).

APPLICATION DETAILS OF USAGE

Dilution : D66 (white spirit).

DRYING TIME

Drying at 20 °C and 60% of humidity :

- * Touch dry : 6 hours.
- * Dry : 12 hours.
- * Recoatable after 24 hours.

STORAGE

Two years in the closed original container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

1 L and 5 L.

HEALTH & SAFETY

Flammable and harmful product.
For more details, consult the Safety data sheet N° 8.

Edition : October 2016 by Colorado (10/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001