




VERNIS V4

Nitro-Cellulose wood varnish
INTERIOR



DESCRIPTION

Varnish based on modified nitro-cellulose resin.

FIELD OF USE

Designed to protect and enhance interior wood giving a smooth and glossy finish.

TECHNICAL CHARACTERISTICS

- Aspect : Gloss.
- Colour : Transparent.
- Spreading-rate : 10 to 12 m²/L depending upon the wood nature, complies with ISO 23811(2009).
- Density : 0.97 +/- 0.05 Kg/L, complies with NM ISO2811-1(2008).
- Viscosity : 2 min +/- 40 secs CF6 at 25°C.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry .

APPLICATION PROPERTIES

VERNIS V4 can be applied by brush, cloth or spray.
Application limit : Do not apply on cold, wet walls below 5°C or conditions of high relative humidity (> 70%).

APPLICATION DETAILS OF USAGE

Dilution : D33 (Cellulosic diluent).

DRYING TIME

- *Touch dry : 5 min.
- *Dry : 15 min.

STORAGE

Two years in the closed container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

850 ml et 4,6 L. (et 20 L by order).

HEALTH & SAFETY

Highly Flammable product.
Can be harmful for the skin and causes death if swallowed or penetrates the respiratory system.
For more details, consult the Safety data sheet N° 03-1.

Edition : October 2016 by Colorado (10/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001