




## VERNIS V5

Nitro-Cellulose wood varnish  
INTERIOR



### DESCRIPTION

High viscosity nitro-cellulose varnish.

### FIELD OF USE

Designed to protect and enhance interior wood giving a smooth and glossy finish to the wood.

### TECHNICAL CHARACTERISTICS

- Aspect : Gloss.
- Colour : Transparent.
- Spreading-rate : 12 to 14 m<sup>2</sup>/L, complies with ISO 23811 (2009).
- Density : 0.97 +/- 0.05 Kg/L to 25°C, complies with NM ISO2811-1(2008).
- Viscosity : 7 min +/- 60 secs with FC6 at 25°C.

### SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound, dry and well prepared.

### APPLICATION PROPERTIES

VERNIS V5 can be applied by brush, cloth or spray.  
Application limit : Do not apply on cold, wet walls below 5°C or conditions of high relative humidity (> 70%).

### APPLICATION DETAILS OF USAGE

Dilution : D33.

### DRYING TIME

Drying at 25 °C and 60% of humidity :

- \* Touch dry : 5 min.
- \* Dry : 20 min +/- 5.
- \* Recoatable after 30 min.

### STORAGE

Two years in the closed original container, as delivered.  
Store inside in conditions avoiding extremes of hot and cold temperatures.

### PACKAGING

0.85 L, 1 L and 4.6 L.

### HEALTH & SAFETY

Information on health, safety and precautions to take are detailed in the Safety data sheet N° 85.

Edition : October 2016 by Colorado (10/16).  
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001