



VERNIS V7

Matt, Nitro-Cellulose based varnish
INTERIOR



DESCRIPTION

Matt varnish based upon modified nitrocellulose resin.

FIELD OF USE

It is designed to enhance and protect interior wood from water and sunlight.
It gives a smooth and flat finish to the wood.

TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Colour : Transparent.
- Spreading-rate : 10 to 12 m²/L, complies with ISO 23811 (2009).
- Density : 0.97 +/- 0.05 Kg/L at 25°C, complies with NM ISO2811-1(2008).
- Viscosity : 2 min +/- 20 secs with the Ford Cup N°6 at 25°C.
- % Solids : 40 +/- 1%, complies with ISO 3233-3(2015).

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering.

APPLICATION PROPERTIES

Substrate conditions: For a quick and easy application the surface should be sound, dry and well prepared.
This varnish can be applied by brush, cloth or spray.
Do not apply on cold, wet walls below 5°C or in conditions of high relative humidity, greater than 70%.

APPLICATION DETAILS FOR USAGE

Diluant : D33 (Diluant Cellulosique).

DRYING TIME

Drying time at 20°C and 60% relative humidity :

- * Touch dry : 5 min.
- * Dry : 15 to 25 min.
- * Recoatable after : 30 min

STORAGE

Two years in the closed can, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures. Keep away from sources of heat, sparks and flames.

PACKAGING

850 ml and 4,6 L (20 L to order).

HEALTH & SAFETY

Highly Flammable, use only in well ventilated areas.
Keep away from sources of heat, sparks and flames.
For more details, consult the safety data sheet N° 06.

Edition : October 2016 by Colorado (10/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certifiée ISO 9001, ISO 14001 an OHSAS 18001